

Chocolate — CH 700 P

Pastry & Chocolate

20 - EN 600 x 400 mm capacity



Technical data

| | |
|---------------------|-----------------------|
| Gross volume | 630 lt |
| Working temperature | +10+18 °C |
| Humidity | 40%-55% |
| Refrigerant | R290 |
| Refrigeration power | 343 W (-10°C / +45°C) |
| Absorption | 279 W |
| Voltage/Frequency | 230V/1~/50Hz |

Refrigeration details

| | |
|------------------------|---|
| Refrigeration unit | Tropicalized and easy extractable monoblock unit. Equipped with low consumption electronic fan motors |
| Refrigerant charge | 110 gr |
| Evaporator | Cataphoresis-treated for high corrosion resistance and installed external to compartment in order to ensure bigger loading capacity |
| Defrost | Automatic by air |
| Condensate evaporation | Automatic through anti-corrosion treated compressor coil |

Construction details

| | |
|----------------------------|---|
| Product dimensions WxDxH | 702x810x2080 |
| Packaging dimensions WxDxH | 770x840x2190 |
| Gross weight | 128 Kg |
| Structure | Stainless steel AISI 304 monocoque |
| External/Internal material | Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel |
| Insulation thickness | 60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP) |
| Inner corners | Rounded for an easy cleaning |
| Door | 1 Self-closing door with 105° door stop. Right hinged, reversible on-site |
| Door gasket | Magnetic and removable, designed to improve insulation and to reduce energy consumption |
| Feet | In AISI 304 stainless steel, height adjustable (90mm-125mm) |

Functions

| | |
|-----------------|---|
| Control panel | High brightness touch screen display with 6 large digits. |
| Open door alarm | Visual and acoustic |
| Functions | Innovative humidity block system: minimum humidity fluctuation (+/-5%), Led lighting ON/OFF, HACCP alarms through Ice connect (optional) |
| Connection | As optional: Remote access through serial interface. Via APP (only Android) it is possible to monitor HACCP traceability, appliance operation and parameters. Graphic and as CVS file export of registered data. Email sending of alarms notification |

Accessories

| | |
|--------------------------|--|
| Lighting | As standard |
| Lock | As standard |
| No. included accessories | 20 - Pair of runners for tray EN 600x400 mm (Mod. 700) |

Options

| | |
|------------------------------------|--------------|
| Aluminum tray EN 600x400 h20 mm | Not included |
| Plastic-coated grid EN 600x800 mm | Not Included |
| Stainless steel grid EN 600x800 mm | Not Included |
| 4 wheels, 2 of which with brake | Not Included |

Versions

| | |
|----------|-----------------------------|
| Versions | Power supply frequency 60Hz |
|----------|-----------------------------|

Technical datasheet EN
Chocolate CH 700 P
Updated on 08-01-2024