

Delizia — DL 700 P BT PV

Pastry and bakery

20 - EN 600 x 400 mm capacity



Technical data

| | |
|---------------------|-----------------------|
| Gross volume | 630 lt |
| Working temperature | -12+22 °C |
| Refrigerant | R290 |
| Refrigeration power | 862 W (-25°C / +45°C) |
| Absorption | 1067 W |
| Voltage/Frequency | 230V/1~/50Hz |

Energy data (UE Reg. 2015/1094)

| | |
|---------------|-------------------|
| Net Volume | 342 lt |
| Climate class | 4 / (30°C - 55%) |

Refrigeration details

| | |
|------------------------|---|
| Refrigeration unit | Tropicalized and easy extractable monoblock unit. Equipped with low consumption electronic fan motors |
| Refrigerant charge | 150 gr |
| Evaporator | Cataphoresis-treated for high corrosion resistance and installed external to compartment in order to ensure bigger loading capacity |
| Defrost | Automatic by hot gas for a shorter cycle and less thermal shocks. Smart defrost is activated only in case of real presence of ice in the evaporator, promoting the energy costs reduction and optimal performance |
| Condensate evaporation | Automatic through anti-corrosion treated compressor coil |

Construction details

| | |
|----------------------------|---|
| Product dimensions WxDxH | 702x815x2080 |
| Packaging dimensions WxDxH | 770x855x2190 |
| Gross weight | 163 Kg |
| Structure | Stainless steel AISI 304 monocoque |
| External/Internal material | Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel |
| Insulation thickness | 60 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP) |
| Inner corners | Rounded for an easy cleaning |
| Door | 1 Self-closing door with 105° door stop. Right hinged, reversible on-site |
| Door gasket | Magnetic and removable, designed to improve insulation and to reduce energy consumption |
| Feet | In AISI 304 stainless steel, height adjustable (90mm-125mm) |

Functions

| | |
|-----------------|---|
| Control panel | High brightness touch screen display with 6 large digits. |
| Open door alarm | Visual and acoustic |
| Functions | Three levels of ventilation intensity management, Led lighting ON/OFF, HACCP alarms through Ice connect (optional) |
| Connection | As optional: Remote access through serial interface. Via APP (only Android) it is possible to monitor HACCP traceability, appliance operation and parameters. Graphic and as CVS file export of registered data. Email sending of alarms notification |

Accessories

| | |
|--------------------------|--|
| Lighting | As standard |
| Lock | As standard |
| No. included accessories | 20 - Pair of runners for tray EN 600x400 mm (Mod. 700) |

Options

| | |
|------------------------------------|--------------|
| Aluminum tray EN 600x400 h20 mm | Not included |
| Plastic-coated grid EN 600x400 mm | Not Included |
| Stainless steel grid EN 600x400 mm | Not Included |
| 4 wheels, 2 with brake | Not Included |

Versions

| | |
|----------|-----------------------------|
| Versions | Power supply frequency 60Hz |
|----------|-----------------------------|

Technical datasheet EN

Delizia DL 700 P BT PV
Updated on 01-01-2024