

Gelato — GL 800 P BT GL 800 P BT plus

Ice-cream

54 x 5lt Tray Capacity (360 x 165 x 120 mm)

48 x 7lt Tray Capacity (360 x 250 x 80 mm)

30 x 7lt Pozzetti Capacity (ø 200 x 250 mm)



Technical data	GL 800 P BT	GL 800 P BT plus
Gross volume	669 lt	669 lt
Working temperature	-12-25 °C	-12-30 °C
Motor type	Plug-in	Plug-in
Refrigerant	R290	R290
Refrigeration power	862 W (-25°C / +45°C)	862 W (-25°C / +45°C)
Absorption	1052 W	1052 W
Voltage/Frequency	230V/1~/50Hz	230V/1~/50Hz

Energy data (UE Reg. 2015/1094)

Net Volume	495 lt	495 lt
Climate class	5 / (40°C - 40%)	5 / (40°C - 40%)
Type	This equipment is intended for use in ambient temperatures up to 40°C	

Refrigeration details

Refrigeration unit	Tropicalized and easy extractable monoblock unit to guarantee liability and performance at 43°C
Refrigerant charge	150 gr
Evaporator	Cataphoresistreated for high corrosion resistance and installed external to compartment in order to ensure bigger loading capacity
Defrost	Automatic by hot gas for a shorter cycle and less thermal shocks. Smart defrost is activated only in case of real presence of ice in the evaporator, promoting the energy costs reduction and optimal performance
Condensate evaporation	Automatic through anti-corrosion treated compressor coil

Construction details

	GL 800 BTG	GL 800 BTG plus
Product dimensions WxDxH	745x870x2120	745x870x2120
Packaging dimensions WxDxH	815x900x2230	815x900x2230
Gross weight	145 Kg	145 Kg
Structure	Stainless steel AISI 304 monocoque	
External/Internal material	Inside and outside in stainless steel AISI 304; internal motor unit compartment, external backside and external bottom in colaminated steel	
Insulation thickness	80 mm of HFO polyurethane to guarantee high insulating properties (very low environmental impact: GWP <5 and zero ODP)	
Inner corners	Rounded for an easy cleaning	
Door	1 Self-closing door with 105° door stop. Right hinged, reversible on-site	
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption	
Feet	In AISI 304 stainless steel, height adjustable (90mm-125mm)	

Functions

Control panel	High brightness touch screen display with 6 large digits.
Open door alarm	Visual and acoustic
Functions	Three levels of ventilation intensity management, Led lighting ON/OFF, HACCP alarms through Ice connect (optional)
Connection	As optional: Remote access through serial interface. Via APP (only Android) it is possible to monitor HACCP traceability, appliance operation and parameters. Graphic and as CVS file export of registered data. Email sending of alarms notification

Accessories

Lighting	Optional
Lock	As standard
No. included accessories	5 - Plastic-coated grid 530x700 mm 5 - Pair of runners for grid 530x700 mm (Mod. 800)

Versions

Versions	Power supply frequency 60Hz
----------	-----------------------------

Technical datasheet EN

GL 800 PBT & 800 PBT plus Ice-cream
 Updated on 06-04-2022